

MXT Series Desiccant Dehumidifier



Product Description

The MXT7500 desiccant dehumidifier is designed to effectively dehumidify high airflow applications using minimal energy. Its airtight construction delivers accurate conditions and optional features provide versatility to adapt the system for specific applications. Its rugged formed metal frame and access panels are produced from corrosion resistant Aluzink®. Standard equipment includes either a base control package or an optional microprocessor-based controller. The electrical control system conforms to EN 60204 (IEC204) standards. The electrical components are mounted on busbars and are constructed of halogen-free plastic. The electrical system is designed for up to 690V and 60° C.

MXT Series dehumidifiers conform to both harmonised European Standards and to CE marking specifications.

Munters Rotor Technology

The desiccant rotor is manufactured from a corrugated composite material that is highly effective at attracting and holding water vapour. Every Munters dehumidifier applies a unique rotor technology. Airflows, air conditions, rotor sections, and rotor rotation speeds are optimised for specific applications. An innovative control system maximises the units energy efficiency. A characteristic of the MX Series rotor technology is the precision seals which divide the air distribution chamber. These provide a precise airflow balance for dehumidification and reactivation while allowing for alternative fan placement and rotor sectioning. Additional sectors for low dewpoints and heat recovery are optional.

PRODUCT INFORMATION

MXT7500

Features

- Dehumidifies efficient down to -20°C.
- High air flow capacity and low energy consumption.
- Reactivation heater choice
 - electrical, steam or gas.
- Microprocessor based control or base control choice.
- Compact design - requires minimal floor area.




The Humidity Expert

Model MXT7500

Diagram measurements are for reference only.

Scaled and dimensioned AutoCAD drawings are available in Munters DryCap program.



Width (A/D)	Depth (B)	Height (C)	Dry air	Wet air	Weight
1000/2206 mm	1213 mm	2172 mm	300x400	150x300	764 kg


Technical Specification

Process air			Gas consumption (m ³ /h)	5,40
Rated airflow (m ³ /h)	7500		Natural gas pressure (mbar)	18-30
Available static pressure (Pa)	300		Max sulphur content (ppm) HPS Rotor	30
Reactivation air			Miscellaneous data	
Rated airflow (m ³ /h)	1660		Operating temperature (°C)	-20/+40
Available static pressure (Pa)	300		Max noise level unducted (dBA)	90
Total power, voltage and current (amps/phase)			Air filter standard	G3
Total power (kW) Electrical	61,08		IEC protective class (unit)	IP44
Total power (kW) Steam/Gas	7,98		IEC protective class (electrical panel)	IP54
200V 3-50/60Hz (A) El.	182,9		MXT (B) Electrical equipment	,
200V 3-50/60Hz (A) St/Gas	29,6		Terminal connection, remote control	Standard
220V 3-50/60Hz (A) El.	167,3		Terminal connection	
220V 3-50/60Hz (A) St/Gas	27,8		general fault alarm	Standard
230V 3-50/60Hz (A) El.	160,1			
230V 3-50/60Hz (A) St/Gas	26,9			
380V 3-50/60Hz (A) El.	96,7			
380V 3-50/60Hz (A) St/Gas	16,0			
400V 3-50 Hz (A) El.	92,0			
400V 3-50 Hz (A) St/Gas	15,5			
415V 3-50 Hz (A) El.	89,1			
415V 3-50 Hz (A) St/Gas	15,3			
440V 3-50 Hz (A) El.	85,2			
440V 3-50 Hz (A) St/Gas	15,6			
500V 3-50 Hz (A) El.	73,5			
500V 3-50 Hz (A) St/Gas	12,3			
Steam consumption (g/s)	25,18			
Max steam working pressure (bar)	7			

Dehumidification Capacity

Approximate capacity in kg/h at different inlet process air relative humidity, % RH.

Dehumidification capacity, kg/h



Options

- Blocked filter alarm
- Rotor stopped alarm
- Remote control with separate control relay
- Humidity control system with alarm and display
- Refer to the RH98 product data sheet
- High capacity EU7 filter (process and reactivation air inlets)
- By-pass channel with damper and actuator
- Reversible assembly for optional left or right hand process air and reactivation air connection
- Stainless steel sheet metal casing