

ML-L Series with Air Cooled Condenser



Product Description

The ML180L desiccant dehumidifier with air cooled condenser is designed to efficiently dehumidify in unheated closed spaces. The wet air from the dehumidifier is passed through the air cooled condenser and then returned to the rotor in a closed loop circuit. The components within the closed loop are constructed of stainless steel and thermoset plastic. Water removed by the condenser is drained away. The heat from the air cooled condenser is then either used in the application or ducted away. Its rugged formed metal frame and access panels are produced from corrosion resistant Aluzink®. The electrical system conforms to established ML-L Series standards as well as to both harmonised European Standards and to CE marking specifications.

Munters Rotor Technology

The desiccant rotor is manufactured from a corrugated composite material that is highly effective at attracting and holding water vapour. Every Munters dehumidifier applies a unique rotor technology. Airflows, air conditions, rotor sections, and rotor rotation speeds are optimised for specific applications. An innovative control system maximises the units energy efficiency. A characteristic of the ML-L Series rotor technology is an extra rotor sector which provides high capacity, while simultaneously recovering heat, thereby effectively reducing the electrical power requirement. The reactivation air is continually re-circulated.

PRODUCT INFORMATION

ML180L

Features

- Heat recovery – condenser heat available.
- Easy to install – no wet air duct needed.
- Dehumidifies efficient down to -0°C.
- Unique plastic rotor casing 100% corrosion resistance.




Munters

The Humidity Expert

Model ML180L

Diagram measurements are for reference only.

Scaled and dimensioned AutoCad drawings are available in Munters DryCap program.



Width (A)	Depth (B)	Height (C)	Diam. (D)	Diam. (E)	Weight
1141 mm	410 mm	910 mm	125 mm	200 mm	113 kg

Technical Specification

Process air

Rated airflow (m³/h)	180
Available static pressure (Pa)	200

Reactivation air

Rated airflow (m³/h)	67
----------------------	----

Condenser air

Rated airflow (m³/h)	650
Available static pressure (Pa)	200
Fan motor power (kW)	0,3
Sensible heat, condenser air (kW)	1,4

Total power, voltage and current (amps/phase)

Total power(kW)	2,57
220V 1-50Hz (A)	12,4
230V 1-50Hz (A)	12,0
240V 1-50Hz (A)	11,7


Miscellaneous data

Operating temperature (°C)	+0/+25
Max noise level unducted (dBA)	75
Air filter standard	G3
IEC protective class (unit)	IP44
IEC protective class (electrical panel)	IP54

Dehumidification Capacity

Approximate capacity in kg/h at different inlet process air relative humidity, % RH.

Dehumidification capacity, kg/h



Options

- Hours run counter (monitors the number of hours the system is operational)
- Humidity control system with alarm and display
Refer to the RH98 product data sheet
- Stainless steel sheet metal casing



www.munters.com

HEADQUARTERS

Munters Europe AB
Tel +46 8 626 6300
Fax +46 8 626 6365
Email:
dehumidification@munters.se

AUSTRIA

Munters GmbH
Tel +43 1 6164298-0
Fax +43 1 6164298-9298
Email:
luftentfeuchtung@munters.at

BELGIUM

Munters N.V.
Tel +32 3 458 24 34
Fax +32 3 458 24 33
Email:
info@muntersnv.be

DENMARK

Munters A/S
Tel +45 4495 3355
Fax +45 4495 3955
Email:
info@munters.dk

FINLAND

Munters OY
Tel +358 9 8386 030
Fax +358 9 8386 0336
Email:
info@munters.fi

FRANCE

Munters France SAS
Tel +33 1 3411 5757
Fax +33 1 3411 5758
Email:
dh@munters.fr

GERMANY

Munters GmbH
Tel +49 40 73416-01
Fax +49 40 73416-131
Email:
mgd@munters.de

ITALY

Munters Italy S.p.A
Tel +39 0183 5211
Fax +39 0183 521 333
Email:
marketing@munters.it

NETHERLANDS

Munters Vochtbeheersing
Tel +31 172 43 32 31
Fax +31 172 44 29 60
Email:
vochtbeheersing@munters.nl

POLAND

Munters Poland Sp. z o.o.
Tel +48 58 320 01 00
Fax +48 58 320 01 19
Email:
dh@munters.pl

SOUTH AFRICA

Munters (Pty) Ltd
Tel +27 11 971 9700
Fax +27 11 971 9701

SPAIN

Munters Spain S.A.
Tel +34 91 640 09 02
Fax +34 91 640 11 32
Email:
marketing@munters.es

SWEDEN

Munters Europe AB
Tel +46 8-626 6300
Fax +46 8-754 8594
Email:
avfuktning@munters.se

SWITZERLAND

Munters GmbH
Tel +41 52 3438886
Fax +41 52 3438887
Email:
info.dh@munters.ch

UNITED KINGDOM

Munters Ltd
Tel +44 1480 432 243
Fax +44 1480 413 147
Email:
info@munters.co.uk